

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
29 November 2001 (29.11.2001)

PCT

(10) International Publication Number
WO 01/89846 A1

- (51) International Patent Classification⁷: **B41J 2/165** (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (21) International Application Number: PCT/AU00/00590
- (22) International Filing Date: 24 May 2000 (24.05.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (*for all designated States except US*): **SILVERBROOK RESEARCH PTY LTD** [AU/AU]; 393 Darling Street, Balmain, New South Wales 2041 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): **SILVERBROOK, Kia** [AU/AU]; Silverbrook Research Pty Ltd, 393 Darling Street, Balmain, New South Wales 2041 (AU).
- (74) Agent: **SILVERBROOK, Kia**; Silverbrook Research Pty Ltd, 393 Darling Street, Balmain, New South Wales 2041 (AU).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: A NOZZLE GUARD FOR AN INK JET PRINTHEAD



(57) Abstract: A nozzle guard (80) for an ink jet printhead includes a body member (82) mountable on a substrate (16) which carries a nozzle array (14). The body member defines a plurality of passages (84) through it such that, in use, each passage (84) is in register with a nozzle opening of one of the nozzles of the array (14). The body member (22) further defines fluid inlet openings (88) for directing fluid through the passages (84), from an inlet end of the passages (84), for inhibiting the build up of foreign particles on the nozzle (14).

WO 01/89846 A1

"A NOZZLE GUARD FOR AN INK JET PRINTHEAD"

FIELD OF THE INVENTION

This invention relates to an ink jet printhead. More particularly, the invention relates to a nozzle guard
for an ink jet printhead.

CO-PENDING APPLICATIONS

Various methods, systems and apparatus relating to the present invention are disclosed in the
following co-pending applications filed by the applicant or assignee of the present invention simultaneously with the
present application:

PCT/AU00/00518, PCT/AU00/00519, PCT/AU00/00520, PCT/AU00/00521, PCT/AU00/00522,
PCT/AU00/00523, PCT/AU00/00524, PCT/AU00/00525, PCT/AU00/00526, PCT/AU00/00527,
PCT/AU00/00528, PCT/AU00/00529, PCT/AU00/00530, PCT/AU00/00531, PCT/AU00/00532,
PCT/AU00/00533, PCT/AU00/00534, PCT/AU00/00535, PCT/AU00/00536, PCT/AU00/00537,
PCT/AU00/00538, PCT/AU00/00539, PCT/AU00/00540, PCT/AU00/00541, PCT/AU00/00542,
PCT/AU00/00543, PCT/AU00/00544, PCT/AU00/00545, PCT/AU00/00547, PCT/AU00/00546,
PCT/AU00/00554, PCT/AU00/00556, PCT/AU00/00557, PCT/AU00/00558, PCT/AU00/00559,
PCT/AU00/00560, PCT/AU00/00561, PCT/AU00/00562, PCT/AU00/00563, PCT/AU00/00564,
PCT/AU00/00565, PCT/AU00/00566, PCT/AU00/00567, PCT/AU00/00568, PCT/AU00/00569,
PCT/AU00/00570, PCT/AU00/00571, PCT/AU00/00572, PCT/AU00/00573, PCT/AU00/00574,
PCT/AU00/00575, PCT/AU00/00576, PCT/AU00/00577, PCT/AU00/00578, PCT/AU00/00579,
PCT/AU00/00581, PCT/AU00/00580, PCT/AU00/00582, PCT/AU00/00587, PCT/AU00/00588,
PCT/AU00/00589, PCT/AU00/00583, PCT/AU00/00593, PCT/AU00/00590, PCT/AU00/00591,
PCT/AU00/00592, PCT/AU00/00584, PCT/AU00/00585, PCT/AU00/00586, PCT/AU00/00594,
PCT/AU00/00595, PCT/AU00/00596, PCT/AU00/00597, PCT/AU00/00598, PCT/AU00/00516,
PCT/AU00/00517, PCT/AU00/00511, PCT/AU00/00501, PCT/AU00/00502, PCT/AU00/00503,
PCT/AU00/00504, PCT/AU00/00505, PCT/AU00/00506, PCT/AU00/00507, PCT/AU00/00508,
PCT/AU00/00509, PCT/AU00/00510, PCT/AU00/00512, PCT/AU00/00513, PCT/AU00/00514,
PCT/AU00/00515

The disclosures of these co-pending applications are incorporated herein by cross-reference.

BACKGROUND TO THE INVENTION

Our co-pending patent application, United States Patent Application Serial Number to be advised when
known (identified temporarily by our Docket No. IJ52) discloses a nozzle guard for an ink jet printhead. The array of
nozzles is formed using microelectromechanical systems (MEMS) technology, and has mechanical structures with sub-
micron thicknesses. Such structures are very fragile, and can be damaged by contact with paper, fingers, and other
objects. The present invention discloses a nozzle guard to protect the fragile nozzles and keep them clear of paper dust.

SUMMARY OF THE INVENTION

According to the invention, there is provided a nozzle guard for an ink jet printhead, the nozzle guard
including a body member mountable on a substrate which carries a nozzle array, the body member defining a plurality of

RECTIFIED SHEET (Rule 91)
ISA/AU

- 1a -

passages through it such that, in use, each passage is in register with a nozzle opening of one of the nozzles of the array and the body member further defining fluid inlet openings for directing fluid through the passages, from an inlet end of said passages, for inhibiting the build up of foreign particles on the nozzle array.

5 In this specification the term "nozzle" is to be understood as an element defining an opening and not the opening itself.

The nozzle guard may include a support means for supporting the body member on the substrate. The support means may be formed integrally with the body member, the support means comprising a pair of spaced support elements one being arranged at each end of the body member.

Then, the fluid inlet openings may be arranged in one of the support elements.

10 It will be appreciated that, when air is directed through the openings, over the nozzle array and out through the passages, a low pressure region is created above the nozzle array which, it is envisaged, will inhibit the build up of foreign particles on the nozzle array.

The fluid inlet openings may be arranged in the support element remote from a bond pad of the nozzle array.

- 2 -

The invention extends also to an ink jet printhead which includes
a nozzle array carried on a substrate; and
a nozzle guard, as described above, mounted on the substrate.

5 The invention extends still further to a method of operating an ink jet printhead, as described above, the method including directing fluid through the fluid inlet openings of the nozzle guard and through the passages to an outlet end of said passages for inhibiting the build up of foreign particles on the nozzle array.

Then, the method may include directing air through the passages irrespective of whether or not ink droplets are being ejected through the passages.

10 The method may include directing fluid through the passages at a rate different from that at which the ink droplets are ejected through the passages. Preferably, the method includes directing the fluid through the passages at a rate lower than that at which the ink droplets are ejected through the passages. In this regard, the air may be charged through the passages at approximately 1m/s. In use, ink is ejected from the nozzle opening of a nozzle of the array at approximately 3m/s and travels through the passage at approximately that velocity.

BRIEF DESCRIPTION OF THE DRAWINGS

15 The invention is now described by way of example with reference to the accompanying diagrammatic drawings in which:-

Figure 1 shows a three dimensional, schematic view of a nozzle assembly for an ink jet printhead;

Figures 2 to 4 show a three dimensional, schematic illustration of an operation of the nozzle assembly of Figure 1;

20 Figure 5 shows a three dimensional view of a nozzle array constituting an ink jet printhead;

Figure 6 shows, on an enlarged scale, part of the array of Figure 5;

Figure 7 shows a three dimensional view of an ink jet printhead including a nozzle guard, in accordance with the invention;

25 Figures 8a to 8r show three dimensional views of steps in the manufacture of a nozzle assembly of an ink jet printhead;

Figures 9a to 9r show sectional side views of the manufacturing steps;

Figures 10a to 10k show layouts of masks used in various steps in the manufacturing process;

Figures 11a to 11c show three dimensional views of an operation of the nozzle assembly manufactured according to the method of Figures 8 and 9; and

30 Figures 12a to 12c show sectional side views of an operation of the nozzle assembly manufactured according to the method of Figures 8 and 9.

DETAILED DESCRIPTION OF THE DRAWINGS

Referring initially to Figure 1 of the drawings, a nozzle assembly, in accordance with the invention is designated generally by the reference numeral 10. An ink jet printhead has a plurality of nozzle assemblies 10 arranged in an ink array 14 (Figures 5 and 6) on a silicon substrate 16. The array 14 will be described in greater detail below.

35 The assembly 10 includes a silicon substrate or wafer 16 on which a dielectric layer 18 is deposited. A CMOS passivation layer 20 is deposited on the dielectric layer 18.

Each nozzle assembly 12 includes a nozzle 22 defining a nozzle opening 24, a connecting member in the form of a lever arm 26 and an actuator 28. The lever arm 26 connects the actuator 28 to the nozzle 22.

40 As shown in greater detail in Figures 2 to 4 of the drawings, the nozzle 22 comprises a crown portion 30 with a skirt portion 32 depending from the crown portion 30. The skirt portion 32 forms part of a peripheral wall of a nozzle chamber 34 (Figures 2 to 4 of the drawings). The nozzle opening 24 is in fluid communication with the nozzle chamber

- 3 -

34. It is to be noted that the nozzle opening 24 is surrounded by a raised rim 36 which "pins" a meniscus 38 (Figure 2) of a body of ink 40 in the nozzle chamber 34.

An ink inlet aperture 42 (shown most clearly in Figure 6 of the drawing) is defined in a floor 46 of the nozzle chamber 34. The aperture 42 is in fluid communication with an ink inlet channel 48 defined through the substrate 16.

5 A wall portion 50 bounds the aperture 42 and extends upwardly from the floor portion 46. The skirt portion 32, as indicated above, of the nozzle 22 defines a first part of a peripheral wall of the nozzle chamber 34 and the wall portion 50 defines a second part of the peripheral wall of the nozzle chamber 34.

10 The wall 50 has an inwardly directed lip 52 at its free end which serves as a fluidic seal which inhibits the escape of ink when the nozzle 22 is displaced, as will be described in greater detail below. It will be appreciated that, due to the viscosity of the ink 40 and the small dimensions of the spacing between the lip 52 and the skirt portion 32, the inwardly directed lip 52 and surface tension function as an effective seal for inhibiting the escape of ink from the nozzle chamber 34.

15 The actuator 28 is a thermal bend actuator and is connected to an anchor 54 extending upwardly from the substrate 16 or, more particularly from the CMOS passivation layer 20. The anchor 54 is mounted on conductive pads 56 which form an electrical connection with the actuator 28.

The actuator 28 comprises a first, active beam 58 arranged above a second, passive beam 60. In a preferred embodiment, both beams 58 and 60 are of, or include, a conductive ceramic material such as titanium nitride (TiN).

20 Both beams 58 and 60 have their first ends anchored to the anchor 54 and their opposed ends connected to the arm 26. When a current is caused to flow through the active beam 58 thermal expansion of the beam 58 results. As the passive beam 60, through which there is no current flow, does not expand at the same rate, a bending moment is created causing the arm 26 and, hence, the nozzle 22 to be displaced downwardly towards the substrate 16 as shown in Figure 3 of the drawings. This causes an ejection of ink through the nozzle opening 24 as shown at 62 in Figure 3 of the drawings. When the source of heat is removed from the active beam 58, i.e. by stopping current flow, the nozzle 22 returns to its quiescent position as shown in Figure 4 of the drawings. When the nozzle 22 returns to its quiescent position, an ink droplet 64 is formed as a result of the breaking of an ink droplet neck as illustrated at 66 in Figure 4 of the drawings. The ink droplet 64 then travels on to the print media such as a sheet of paper. As a result of the formation of the ink droplet 64, a "negative" meniscus is formed as shown at 68 in Figure 4 of the drawings. This "negative" meniscus 68 results in an inflow of ink 40 into the nozzle chamber 34 such that a new meniscus 38 (Figure 2) is formed in readiness for the next ink drop ejection from the nozzle assembly 10.

30 Referring now to Figures 5 and 6 of the drawings, the nozzle array 14 is described in greater detail. The array 14 is for a four color printhead. Accordingly, the array 14 includes four groups 70 of nozzle assemblies, one for each color. Each group 70 has its nozzle assemblies 10 arranged in two rows 72 and 74. One of the groups 70 is shown in greater detail in Figure 6 of the drawings.

35 To facilitate close packing of the nozzle assemblies 10 in the rows 72 and 74, the nozzle assemblies 10 in the row 74 are offset or staggered with respect to the nozzle assemblies 10 in the row 72. Also, the nozzle assemblies 10 in the row 72 are spaced apart sufficiently far from each other to enable the lever arms 26 of the nozzle assemblies 10 in the row 74 to pass between adjacent nozzles 22 of the assemblies 10 in the row 72. It is to be noted that each nozzle assembly 10 is substantially dumbbell shaped so that the nozzles 22 in the row 72 nest between the nozzles 22 and the actuators 28 of adjacent nozzle assemblies 10 in the row 74.

40 Further, to facilitate close packing of the nozzles 22 in the rows 72 and 74, each nozzle 22 is substantially hexagonally shaped.

- 4 -

It will be appreciated by those skilled in the art that, when the nozzles 22 are displaced towards the substrate 16, in use, due to the nozzle opening 24 being at a slight angle with respect to the nozzle chamber 34 ink is ejected slightly off the perpendicular. It is an advantage of the arrangement shown in Figures 5 and 6 of the drawings that the actuators 28 of the nozzle assemblies 10 in the rows 72 and 74 extend in the same direction to one side of the rows 72 and 74.

Hence, the ink ejected from the nozzles 22 in the row 72 and the ink ejected from the nozzles 22 in the row 74 are offset with respect to each other by the same angle resulting in an improved print quality.

Also, as shown in Figure 5 of the drawings, the substrate 16 has bond pads 76 arranged thereon which provide the electrical connections, via the pads 56, to the actuators 28 of the nozzle assemblies 10. These electrical connections are formed via the CMOS layer (not shown).

Referring to Figure 7 of the drawings, a development of the invention is shown. With reference to the previous drawings, like reference numerals refer to like parts, unless otherwise specified.

In this development, a nozzle guard 80 is mounted on the substrate 16 of the array 14. The nozzle guard 80 includes a body member 82 having a plurality of passages 84 defined therethrough. The passages 84 are in register with the nozzle openings 24 of the nozzle assemblies 10 of the array 14 such that, when ink is ejected from any one of the nozzle openings 24, the ink passes through the associated passage before striking the print media.

The body member 82 is mounted in spaced relationship relative to the nozzle assemblies 10 by limbs or struts 86. One of the struts 86 has air inlet openings 88 defined therein.

In use, when the array 14 is in operation, air is charged through the inlet openings 88 to be forced through the passages 84 together with ink travelling through the passages 84.

The ink is not entrained in the air as the air is charged through the passages 84 at a different velocity from that of the ink droplets 64. For example, the ink droplets 64 are ejected from the nozzles 22 at a velocity of approximately 3m/s. The air is charged through the passages 84 at a velocity of approximately 1m/s.

The purpose of the air is to maintain the passages 84 clear of foreign particles. A danger exists that these foreign particles, such as dust particles, could fall onto the nozzle assemblies 10 adversely affecting their operation. With the provision of the air inlet openings 88 in the nozzle guard 80 this problem is, to a large extent, obviated.

Referring now to Figures 8 to 10 of the drawings, a process for manufacturing the nozzle assemblies 10 is described.

Starting with the silicon substrate or wafer 16, the dielectric layer 18 is deposited on a surface of the wafer 16. The dielectric layer 18 is in the form of approximately 1.5 microns of CVD oxide. Resist is spun on to the layer 18 and the layer 18 is exposed to mask 100 and is subsequently developed.

After being developed, the layer 18 is plasma etched down to the silicon layer 16. The resist is then stripped and the layer 18 is cleaned. This step defines the ink inlet aperture 42.

In Figure 8b of the drawings, approximately 0.8 microns of aluminum 102 is deposited on the layer 18. Resist is spun on and the aluminum 102 is exposed to mask 104 and developed. The aluminum 102 is plasma etched down to the oxide layer 18, the resist is stripped and the device is cleaned. This step provides the bond pads and interconnects to the ink jet actuator 28. This interconnect is to an NMOS drive transistor and a power plane with connections made in the CMOS layer (not shown).

Approximately 0.5 microns of PECVD nitride is deposited as the CMOS passivation layer 20. Resist is spun on and the layer 20 is exposed to mask 106 whereafter it is developed. After development, the nitride is plasma etched down to the aluminum layer 102 and the silicon layer 16 in the region of the inlet aperture 42. The resist is stripped and the device cleaned.

- 5 -

A layer 108 of a sacrificial material is spun on to the layer 20. The layer 108 is 6 microns of photo-sensitive polyimide or approximately 4 μm of high temperature resist. The layer 108 is softbaked and is then exposed to mask 110 whereafter it is developed. The layer 108 is then hardbaked at 400°C for one hour where the layer 108 is comprised of polyimide or at greater than 300°C where the layer 108 is high temperature resist. It is to be noted in the drawings that the pattern-dependent distortion of the polyimide layer 108 caused by shrinkage is taken into account in the design of the mask 110.

In the next step, shown in Figure 8e of the drawings, a second sacrificial layer 112 is applied. The layer 112 is either 2 μm of photo-sensitive polyimide which is spun on or approximately 1.3 μm of high temperature resist. The layer 112 is softbaked and exposed to mask 114. After exposure to the mask 114, the layer 112 is developed. In the case of the layer 112 being polyimide, the layer 112 is hardbaked at 400°C for approximately one hour. Where the layer 112 is resist, it is hardbaked at greater than 300°C for approximately one hour.

A 0.2 micron multi-layer metal layer 116 is then deposited. Part of this layer 116 forms the passive beam 60 of the actuator 28.

The layer 116 is formed by sputtering 1,000Å of titanium nitride (TiN) at around 300°C followed by sputtering 50Å of tantalum nitride (TaN). A further 1,000Å of TiN is sputtered on followed by 50Å of TaN and a further 1,000Å of TiN.

Other materials which can be used instead of TiN are TiB₂, MoSi₂ or (Ti, Al)N.

The layer 116 is then exposed to mask 118, developed and plasma etched down to the layer 112 whereafter resist, applied for the layer 116, is wet stripped taking care not to remove the cured layers 108 or 112.

A third sacrificial layer 120 is applied by spinning on 4 μm of photo-sensitive polyimide or approximately 2.6 μm high temperature resist. The layer 120 is softbaked whereafter it is exposed to mask 122. The exposed layer is then developed followed by hard baking. In the case of polyimide, the layer 120 is hardbaked at 400°C for approximately one hour or at greater than 300°C where the layer 120 comprises resist.

A second multi-layer metal layer 124 is applied to the layer 120. The constituents of the layer 124 are the same as the layer 116 and are applied in the same manner. It will be appreciated that both layers 116 and 124 are electrically conductive layers.

The layer 124 is exposed to mask 126 and is then developed. The layer 124 is plasma etched down to the polyimide or resist layer 120 whereafter resist applied for the layer 124 is wet stripped taking care not to remove the cured layers 108, 112 or 120. It will be noted that the remaining part of the layer 124 defines the active beam 58 of the actuator 28.

A fourth sacrificial layer 128 is applied by spinning on 4 μm of photo-sensitive polyimide or approximately 2.6 μm of high temperature resist. The layer 128 is softbaked, exposed to the mask 130 and is then developed to leave the island portions as shown in Figure 9k of the drawings. The remaining portions of the layer 128 are hardbaked at 400°C for approximately one hour in the case of polyimide or at greater than 300°C for resist.

As shown in Figure 8l of the drawing a high Young's modulus dielectric layer 132 is deposited. The layer 132 is constituted by approximately 1 μm of silicon nitride or aluminum oxide. The layer 132 is deposited at a temperature below the hardbaked temperature of the sacrificial layers 108, 112, 120, 128. The primary characteristics required for this dielectric layer 132 are a high elastic modulus, chemical inertness and good adhesion to TiN.

A fifth sacrificial layer 134 is applied by spinning on 2 μm of photo-sensitive polyimide or approximately 1.3 μm of high temperature resist. The layer 134 is softbaked, exposed to mask 136 and developed. The remaining portion of the layer 134 is then hardbaked at 400°C for one hour in the case of the polyimide or at greater than 300°C for the resist.

- 6 -

The dielectric layer 132 is plasma etched down to the sacrificial layer 128 taking care not to remove any of the sacrificial layer 134.

This step defines the nozzle opening 24, the lever arm 26 and the anchor 54 of the nozzle assembly 10.

5 A high Young's modulus dielectric layer 138 is deposited. This layer 138 is formed by depositing 0.2 μ m of silicon nitride or aluminum nitride at a temperature below the hardbaked temperature of the sacrificial layers 108, 112, 120 and 128.

10 Then, as shown in Figure 8p of the drawings, the layer 138 is anisotropically plasma etched to a depth of 0.35 microns. This etch is intended to clear the dielectric from all of the surface except the side walls of the dielectric layer 132 and the sacrificial layer 134. This step creates the nozzle rim 36 around the nozzle opening 24 which "pins" the meniscus of ink, as described above.

An ultraviolet (UV) release tape 140 is applied. 4 μ m of resist is spun on to a rear of the silicon wafer 16. The wafer 16 is exposed to mask 142 to back etch the wafer 16 to define the ink inlet channel 48. The resist is then stripped from the wafer 16.

15 A further UV release tape (not shown) is applied to a rear of the wafer 16 and the tape 140 is removed. The sacrificial layers 108, 112, 120, 128 and 134 are stripped in oxygen plasma to provide the final nozzle assembly 10 as shown in Figures 8r and 9r of the drawings. For ease of reference, the reference numerals illustrated in these two drawings are the same as those in Figure 1 of the drawings to indicate the relevant parts of the nozzle assembly 10. Figures 11 and 12 show the operation of the nozzle assembly 10, manufactured in accordance with the process described above with reference to Figures 8 and 9 and these figures correspond to Figures 2 to 4 of the drawings.

20 It will be appreciated by persons skilled in the art that numerous variations and/or modifications may be made to the invention as shown in the specific embodiments without departing from the spirit or scope of the invention as broadly described. The present embodiments are, therefore, to be considered in all respects as illustrative and not restrictive.

- 7 -

THE CLAIMS

1. A nozzle guard for an ink jet printhead, the nozzle guard including a body member mountable on a substrate which carries a nozzle array, the body member defining a plurality of passages through it such that, in use, each passage is in register with a nozzle opening of one of the nozzles of the array and the body member further defining fluid inlet openings for directing fluid through the passages, from an inlet end of said passages, for inhibiting the build up of foreign particles on the nozzle array.

2. The nozzle guard of Claim 1 which, includes a support means for supporting the body member on the substrate.

3. The nozzle guard of Claim 2 in which the support means is formed integrally with the body member, the support means comprising a pair of spaced support elements, one element being arranged at each end of the body member.

4. The nozzle guard of Claim 3 in which the fluid inlet openings are arranged in one of the support elements.

5. The nozzle guard as claimed in Claim 4 in which the fluid inlet openings are arranged in the support element remote from a bond pad of the nozzle array.

6. An ink jet printhead which includes
a nozzle array carried on a substrate; and
a nozzle guard, as claimed in Claim 1, mounted on the substrate.

7. A method of operating an ink jet printhead as claimed in Claim 6, the method including directing fluid through the fluid inlet openings of the nozzle guard and through the passages to an outlet end of said passages for inhibiting the build up of foreign particles on the nozzle array.

8. The method of Claim 7 which includes directing air through the passages irrespective of whether or not ink droplets are being ejected through the passages.

9. The method of Claim 8 which includes directing fluid through the passages at a rate different from that at which the ink droplets are ejected through the passages.

10. The method of Claim 9 which includes directing the fluid through the passages at a rate lower than that at which the ink droplets are ejected through the passages.

1/27







FIG. 1



3/27




FIG. 5

4/27





FIG. 6

5/27



6/27





FIG. 10a

7/27




FIG. 8b




FIG. 9b









FIG. 10b




8/27



9/27



10/27



11/27




FIG. 8f









FIG. 9f

12/27



13/27



14/27




FIG. 8i




FIG. 9i

15/27




FIG. 8j




FIG. 9j




FIG. 10h




FIG. 8k




FIG. 9k




FIG. 10i

17/27




FIG. 81









FIG. 91

18/27



19/27



20/27




FIG. 80






FIG. 90

21/27



22/27




FIG. 8q

23/27







FIG. 10k

24/27



25/27




FIG. 11a




FIG. 12a

26/27




FIG. 11b




FIG. 12b

27/27




FIG. 11c




FIG. 12c

INTERNATIONAL SEARCH REPORT

 International application No.
PCT/AU00/00590

A. CLASSIFICATION OF SUBJECT MATTER				
Int. Cl. ⁷ : B41J 2/165				
According to International Patent Classification (IPC) or to both national classification and IPC				
B. FIELDS SEARCHED				
Minimum documentation searched (classification system followed by classification symbols) ELECTRONIC SEARCH AS BELOW				
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched				
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) WPAT, JAPIO				
C. DOCUMENTS CONSIDERED TO BE RELEVANT				
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.		
X	US 5929877 A (HETZER et al.) 27 July 1999 See figures 1 and 2, column 3 lines 34 to 58	1 to 10		
X	US 5877788 A (HAAN et al.) 2 March 1999 See figure 1, column 2 lines 33 to 38, column 3 lines 7 to 15.	1 to 10		
X	US 4417259 A (MAEDA) 22 November 1983 See figure 1, column 3 lines 8 to 27	1 to 10		
<input type="checkbox"/> Further documents are listed in the continuation of Box C <input checked="" type="checkbox"/> See patent family annex				
<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; vertical-align: top;"> <p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier application or patent but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </td> <td style="width: 50%; vertical-align: top;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p> </td> </tr> </table>			<p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier application or patent but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p>	<p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p>
<p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier application or patent but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p>	<p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p>			
Date of the actual completion of the international search 4 August 2000		Date of mailing of the international search report 15 SEP 2000		
Name and mailing address of the ISA/AU AUSTRALIAN PATENT OFFICE PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaustalia.gov.au Facsimile No. (02) 6285 3929		Authorized officer PETER T. WEST Telephone No : (02) 6283 2108		

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.
PCT/AU00/00590

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report	Patent Family Member					
US 5929877	DE 19522593	EP 749836				
US 5877788	AU 55400/96	CA 2218984	CN 1183078	EP 824403	NZ 306756	
	WO 9635584					
US 4417259	DE 3203014	FR 2498989	JP 5719754			
						END OF ANNEX

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)